



Frescolithe Exhibition- and Scenery Paint

DESCRIPTION	Water-borne exhibition- and scenery paint for indoor use based on a synthetic resin dispersion.
FEATURES	Bright colors and excellent hide. Ultra mat. Solvent-free and low odor. Quick drying, multiple layers possible in one day. Easy to apply, no blocking. For indoor use.
APPLICATION	Ideally suited as a finish for stand construction, television and theater sets, photo studios, limbo's, various sheet materials and plastics. In diluted form suitable for use on theater screens.
COLORS	Neverlak 6000/Emotions color palette, Eurotrend, NCS, Pantone (approximate), RAL and colors according to sample or from color palettes other then mentioned above.
GLOSS LEVEL	Ultra mat.
PACKAGING	4 and 12.5 kg. (Except White Extra 4 and 15 kg, Superexpo White 15 kg.).
BASIC DETAILS	Drying time determined at 23°C and 50% relative humidity. Density : 1.4 -1.5 kg / dm ³ . Depending on the color. To Touch : approximately 30 minutes. Dry : approximately 1 hours. To Recoat : approximately 2 hours. To Full Cure : after 30 days. Potlife : at least 12 months in closed original packaging. Keep in a cool, dry and frost-free place. V.O.C. : class A / a. 30 g / l. (2010) max. 30 g / l.
COVERAGE	Approximately 5-7 sq. meters per kg on smooth, nonporous surfaces depending on the method of processing and the nature and structure of the substrate.
PROCESSING	Processing method : easy to process with a brush, roller or sprayer. : stir well before use.

: Airless;
pressure: 160 bar.
tip: 5/15 – 5/17.
: HVLP air sprayer;
pressure: 3 bar.
nozzle opening: 2 mm
: Air spray;
pressure: 3 bar.
nozzle opening:
1.5 – 2mm.

Processing conditions : apply when air, product and
Surface temperatures are
between 5°C and 28°C.
: relative air humidity max 85%.
: ensure good ventilation.
Dilution : water, with a maximum of
10 %.

SUBSTRATE TREATMENT

The surface must be clean, dry, free of grease and any other surface contaminants.
Treat seams, tears and holes with a suitable filler (for instance Decofoam) and let it dry thoroughly.
Impregnate porous surfaces with Putop Impregnate.

CLEANING TOOLS

Immediately after use with water.

TECHNICAL ADVICE

For advice, please contact:
Neverlak B.V. T : 0031 (0) 20 6655 678
E : info@neverlak.nl

The information mentioned above is entirely without obligation and is based on your own observations and experiences. Our information counts as non-committal advice and does not release the customer / processor from the obligation to test the products supplied by us before proceeding to the processing process. The application and processing of our products takes place outside of our control capabilities and observation and therefore solely for the responsibility of the buyer / processor.

Upon the publication of a new edition of this Technical Data Sheet, this publication loses its validity.