



NEVERLAK B.V.

Duivendrechtsekade 90, 1096 AJ Amsterdam
T +31 (0)20 665 56 78
E info@neverlak.nl W www.neverlak.nl
KvK 33012200 • BTW NL 001466550 B01
IBAN: NL87 RABO 0102 8336 21
BIC: RABONL2U

PRODUCTINFORMATION

DECEMBER 2016

FRESCOLITHE METALLIC

DESCRIPTION	High-quality water-borne metal effect wallpaint for indoor use based on acrylic polymer.
FEATURES	Unique metallic shine. Bright colors and excellent hide. Solvent-free and low odor. Quick drying, multiple layers possible in one day. Easy to apply.
APPLICATION	Suitable for processing on various surfaces such as plaster, masonry, plasterboard, wood wool cement panels, concrete and fibreglass-wallpaper.
COLORS	235 (see Neverlak 8000 color palette).
GLOSS LEVEL	Satin gloss.
PACKAGING	4 and 10 kg.
BASIC DETAILS	Drying time determined at 23°C and 50% relative humidity. Density : 1.2 kg / dm ³ . To Touch : approximately 1 hour. Dry : approximately 2 hours. To Recoat : approximately 4 hours. To Full Cure : after 30 days. Potlife : at least 12 months in closed original packaging. Keep in a cool, dry and frost-free place. V.O.C. : class A / a. 30 g / l. (2010) max. 5 g / l.
COVERAGE	Approximately 7-9 sq. meters per liter on smooth, nonporous surfaces depending on the method of processing and the nature and structure of the substrate.
PROCESSING	Processing method sprayer : preferably process with a paint sprayer. : Air sprayer; spray pressure: 3-4 bar. nozzle opening: 1.5-2 mm. : HVLP air sprayer; spray pressure: 3-4 bar. nozzle opening: 1.8 mm

: Airmix;
spray pressure airless pump:
from 50 bar.
Air pressure: 3-4 bar.
tip: 4/13.

Processing method brush or roller : stir well before use.
: processing with brush or roller
(nylon) is possible. Due to the
metallic effect and gloss level,
visible overlaps will be seen
sooner.
When processing with a roll,
always roll in one direction.

Processing conditions : apply when air, product and
Surface temperatures are
between 5°C and 28°C.
: relative air humidity max 85%.
: ensure good ventilation.
Dilution : water, preferably use undiluted.

SUBSTRATE TREATMENT

The surface must be clean, dry, free of grease and any
other surface contaminants.
Impregnate porous surfaces with Putop Impregnate.
After possible impregnation, pre-treat the surface with
Putop Supreme in a color corresponding to the Frescolithe
Metallics.

CLEANING TOOLS

Immediately after use with water.

TECHNICAL ADVICE

For advice, please contact:
Neverlak B.V. T : 0031 (0) 20 6655 678
E : info@neverlak.nl

The information mentioned above is entirely without obligation and is based on your own observations and experiences. Our information counts as non-committal advice and does not release the customer / processor from the obligation to test the products supplied by us before proceeding to the processing process. The application and processing of our products takes place outside of our control capabilities and observation and therefore solely for the responsibility of the buyer / processor.

Upon the publication of a new edition of this Technical Data Sheet, this publication loses its validity.