



PRODUCT INFORMATION

MARCH 2016

PUTOP SUPREME

DESCRIPTION	Water-borne eggshell gloss wall paint for indoors based on an acrylic dispersion.
FEATURES	Bright colors and excellent hide. Easy to sand and scrub resistant. Easy to clean, resistant to the usual cleaning products. Easy to process. Block-resistant (after 7 days of curing).
APPLICATION	Suitable for stand and interior construction where a high-quality product is required. For an eggshell gloss, easy to clean finish on interior walls. Putop Supreme is the ideal substrate for Frescolithe Metallics.
COLORS	Neverlak 6000- and Emotions color palette, Eurotrend, NCS, Pantone (approximate), RAL and colours according to sample or from color palettes other than mentioned above.
GLOSS LEVEL	Eggshell gloss (8-10%).
PACKAGING	4 and 12 kg.
BASIC DETAILS	Drying time determined at 23°C and 50% relative humidity. Density : 1,4 kg / dm ³ . To Touch : approximately 1 hour. Dry : approximately 2 hours. To Recoat : approximately 4 hours. To Full Cure : after 30 days. Potlife : at least 12 months in closed original packaging. Keep in a cool, dry and frost-free place. V.O.C. : class A / a. 30 g / l. (2010) max. 30 g / l.
COVERAGE	Approximately 5-7 sq. meters per kg on smooth, nonporous surfaces. Depending on the method of processing and the nature and structure of the substrate.
PROCESSING	Processing method : easy to process with a brush or roller. : excellent for spraying with an airless- and or air sprayer. : when processed with an airless pressure 180–190 bar, tip 4/15.

Processing condition : apply when air, product and surface temperatures are between 5°C and 28°C.
: relative air humidity max. 80%.
: ensure good ventilation.
Dilution : max. 5% water.

SUBSTRATE TREATMENT

Surfaces must be clean, dry and non-porous. Remove all loose, peeling paint, dirt, grease and any other surface contaminants. Impregnate porous surfaces such as plaster, sand-lime brick, aerated-concrete, etc. with Putop Impregnate. Putop Supreme can be applied directly in two layers on non-porous surfaces, with a drying time of approximately 4 hours between the two layers.

CLEANING TOOLS

Clean with water immediately after use.

SAFETY REGULATIONS

For safety instructions, see the Safety Data Sheet.

TECHNICAL ADVICE

For advice please contact:
Neverlak B.V. T : 0031 (0) 20 6655 678
E : info@neverlak.nl

The information mentioned above is entirely without obligation and is based on your own observations and experiences. Our information counts as non-committal advice and does not release the customer / processor from the obligation to test the products supplied by us before proceeding to the processing process. The application and processing of our products takes place outside of our control capabilities and observation and therefore solely for the responsibility of the buyer / processor.

Upon the publication of a new edition of this Technical Data Sheet, this publication loses its validity.